

Single phase string inverters 1 to 3 kW

# ASW S-S Series



Models:

ASW1000S-S

ASW1500S-S

ASW2000S-S

ASW3000S-S



## Easy-to-install

- Quick & easy-to-install with basic tools
- Compact, wall mount and SUNCLIX connection
- Quick Wi-Fi set up with app



## Reliable

- International quality standards
- Integrated 150% range DC/AC switch
- IP65 waterproof for outdoor use



## User-friendly

- Smart monitoring with user-friendly app
- Discrete design that fits anywhere
- Quiet performance with low 15dB levels



# Technical Data Sheet

ASW1000S-S

ASW1500S-S

ASW2000S-S

ASW3000S-S

Input (DC)	Max PV array power	1500 Wp STC	2250 Wp STC	3000 Wp STC	4500 Wp STC
	Max input voltage	580 V			
	MPP voltage range / rated input voltage	80 V to 550 V / 360 V			
	Min input voltage	80 V			
	Initial feed-in voltage	100 V			
	Max operating input current	12 A			
	Max short circuit current	18 A			
	Number of independent MPP inputs / strings per MPP input	1/1			
Output (AC)	Rated power	1000 W	1500 W	2000 W	3000 W
	Max apparent AC power	1000 VA	1500 VA	2000 VA	3000 VA
	AC nominal voltage	220 V / 230 V / 240 V			
	AC voltage range	180 V to 290 V			
	AC grid frequency / range	50 Hz / 45 Hz to 55 Hz – 60 Hz / 55 Hz to 65 Hz			
	Rated grid frequency / rated grid voltage	50 Hz / 230 V			
	Max output current	5 A	7.5 A	10 A	13.6 A
	Power factor at rated power	1			
	Adjustable displacement power factor	0.8 overexcited to 0.8 underexcited			
	Feed-in phases	1			
	Harmonic distortion (THD) at rated output	<3%			
Efficiency & Protection	Max efficiency / European efficiency	97.4%/95.4%	97.6%/96.3%	97.6%/96.8%	97.6%/97.1%
	Input-side disconnection device	●			
	Ground fault monitoring / grid monitoring	● / ●			
	DC reverse polarity protection / AC short circuit current capability	● / ●			
	All-pole-sensitive residual-current monitoring unit	●			
	Protection class (according to IEC 62109-1) / overvoltage category (according to IEC 62109-1)	1/AC: III; DC :II			
General data	Dimensions (W / H / D)	320/264/94 mm			
	Weight	6.5 kg			
	Operating temperature range	-25°C – +60°C			
	Noise emission (typical)	< 15 dB(A)			
	Self-consumption (at night)	<1W			
	Topology	Transformerless			
	Cooling concept	Convection			
	Degree of protection (according to IEC 60529)	IP65			
	Climatic category (according to IEC 60721-3-4)	4K4H			
	Max permissible value for relative humidity (non-condensing)	100 %			
Max operating altitude	3000 m				
Features	DC connection	SUNCLIX (Phoenix Contact)			
	AC connection	Plug-in Connector			
	Mounting type	Wall-mounting bracket			
	LED Indicators (Status / Fault/ Communication)	●			
	Communication interface <sup>1&amp;2</sup>	Wi-Fi / RS485			
	Certificates and approvals (more available on request)	CE, IEC62109, IEC61000, EN50549, AS/NZS4777, C10/C11, IEC61727, IEC62116, IEC61683			

● Standard features / ○ optional features / – not available

1- Zero export installations supported with 2-pin RS485 for connection to approved smart meters

2- DRED supported with RS485 communication for Australia & New Zealand

Version: April 2021

