

GRENTON ROLLER SHUTTER

RSH-044-T-02

ROLLER SHUTTER CONTROL MODULE
FOR FLUSH-MOUNT ASSEMBLY



Allows you to control any roller shutter drive.

- equipped with two control contacts (up/down, left/right)
- small size - fits into a P60 box under the ancillary equipment
- allows you to control drives with a maximum capacity of 1.8 kVA

CONFIGURATION PARAMETERS

CHARACTERISTICS

Name	Description
M1	State of M1 relay
M2	State of M2 relay
State	Device state. 0 - no movement, 1 - moving downwards, 2 - moving upwards
MaxTime	Default Time parameter value. Maximum movement time

METHODS

Name	Description
Up	Roller Shutter Up or Stop if moving. Parameter Time: - 0 - output is active for the time specified in MaxTime - number - output is active for specified time
Down	Roller Shutter Down or Stop if moving. Parameter Time: - 0 - output is active for the time specified in MaxTime - number - output is active for specified time
Start	Roller Shutter Up if the preceding motion was Down or Roller Shutter Down if the preceding motion was Up. Parameter Time: - 0 - output is active for the time specified in MaxTime - number - output is active for specified time
Stop	Stop if moving
Hold	Hold with direction change
HoldUp	Hold always up
HoldDown	Hold always down

EVENTS

Name	Description
OnChange	Occurs when changing the state of any of the outputs
OnUp	Occurs when changing the Stop state to the Up state
OnDown	Occurs when changing the Stop state to the Down state
OnStart	Occurs when Start is requested
OnStop	Occurs when Stop is requested

TECHNICAL SPECIFICATIONS

DC supply	5 V
average current input	4.18 mA
max. current input	112 mA
weight	46 g
dimensions (H/W/D)	52/57/21mm
max. connection wire section	$\leq 1.5\text{mm}^2$
operating temperature range	0 to +40°C
maximum load	1,800 VA

WIRING DIAGRAM

