

---

**Concrete-mounted enclosure for EM/FLB-HTD-760 box**

**Code: EM/FLB-HTD-760-PJB**

**Description and Technical Characteristics of the Product:**

Concrete-mounted enclosure (box) for EM/FLB-HTD-760 box with frame. Allows installation in a drilled hole or in poured concrete.



**Installation method:**

**in concrete:**

drill a hole in the floor, cut holes for cable entry in concrete-mounted box (code: EM/FLB-HTD-760PJB), adjust the depth to the depth of the EM/FLB-HTD-760 frame, place the box in the required location on the floor, fixing it to the floor with screws, if necessary, level it, insert the wires into the box placed in concrete; insert the wires into the box with frame through the previously cut holes; screw the box with frame to the box placed in the concrete using the existing mounting screws.

**in poured concrete:**

cut holes for cable entry in concrete-mounted box (code: EM/FLB-HTD-760PJB), adjust the depth to the depth of the EM/FLB-HTD-760 frame, place the box in the required place on the floor (if necessary, drill a deeper hole), fixing it to the floor with screws, if necessary, level it, insert the wires into the box placed in concrete; after pouring concrete, insert the wires into the box with frame through the previously cut holes; screw the box with frame to the box placed in the concrete using the existing mounting screws.

**Markings:**

Concrete-mounted enclosure for EM/FLB-HTD-760 box; code: EM/FLB-HTD-760-PJB

**Products compatible with the enclosure:**

12-module floor box for mounting fixtures 22.5x45 (45x45); code: EM/FLB-HTD-760

Note: Due to the different depth of the sockets and the different ways of routing and connecting the cables, some sockets in the adapters may not be compatible. Due to the possibility of different component combinations, it is recommended to check this or contact the technical department before installation.

**Enclosure (box):**

finish: ABS plastic

colour - grey

dimensions (W x H ): 220x 220mm (outline) ; D adjustable 80-120mm

Weight 0.4kg

The product designed for floors for dry floor treatments. The product is designed for installation in places, in which its functionality and application will be used. For this reason, do not design the installation of a floor box in walkways and areas, in which they will be a hindrance or obstacle to people moving around.

Depending on the type and number of cables and connection wires plugged into the box-mounted sockets, the cover may or may not fully close. Appropriate functionality, resulting from the product features, should be envisioned by the designer at the design stage.

We have made every effort to ensure that the information presented is accurate and complete. However, we are not responsible for the accuracy and completeness of the data and, in particular, we cannot guarantee that this specification does not contain errors or mistakes. The information contained in this specification may be changed at any time without notice.