

EmiterNet 19" wall-mounted non-divided lightweight cabinet

| | | |
|-------|-----------------|--|
| code: | EM/SH02B5404-08 | 19"4U lightweight wall cabinet, non-divided |
| | EM/SH02B5406-08 | 19" 6U lightweight wall cabinet, non-divided |
| | EM/SH02B5409-08 | 19"9U lightweight wall cabinet, non-divided |
| | EM/SH02B5412-08 | 19"12U lightweight wall cabinet, non-divided |

Description and Technical Characteristics of the Product:

The framework of the cabinet is made of powder-coated steel sheet.
The enclosure has two cable exit holes (340x65mm 1x top section, 1x bottom section).
Front door with glued-in tempered glass and 1-point lock, mounted on hinges that allow the door to open 180 degrees. The door can be repositioned to open the other way.
Removable side covers (no lock). Two 19" planes of vertical mounting profiles, mounted on horizontal beams.
Maximum profile spacing: 380mm (250mm as standard).
There are holes in the roof of the cabinet adapted for the installation of one ventilation module with 1 fan for the cabinets up to 9U and two modules with 1 fan for 12U cabinets There are 4 holes with a diameter of 12 mm in the rear wall spaced 400x115mm apart for mounting the cabinet on the wall.



Cabinet standard equipment:

10 sets of mounting screws

The cabinets are designed for indoor use for light applications.

There are also longitudinal knockouts/cut-outs (also for screws) in the bottom and roof of the cabinets (depends on the model of the cabinet and when it was manufactured), where the EmitterNet wall cabinet brush grommet can be used.

Compatible products:

BK/24011100 1-fan ventilation module mounted in wall cabinets

Technical parameters:

Cabinet colour RAL 9004 (black - structure)

Two 19" mounting planes

Degree of protection against solids and dust and against water ingress: IP 20 (does not apply to cabinets with brush grommets installed).

Fully-assembled cabinet

The cabinets are packed in a cardboard box

Markings:

| code | carrying capacity | width | depth | height [U] | height [mm] | weight [kg] |
|-----------------|-------------------|-------|-------|------------|-------------|-------------|
| EM/SH02B5404-08 | 30 kg | 550 | 450 | 4 | 230 | 14 |
| EM/SH02B5406-08 | 30 kg | 550 | 450 | 6 | 320 | 16 |
| EM/SH02B5409-08 | 40 kg | 550 | 450 | 9 | 455 | 19 |
| EM/SH02B5412-08 | 40 kg | 550 | 450 | 12 | 590 | 22 |

Note 1: dimensions are given in millimetres!

Note 2: A cabinet for lightweight applications, with a small carrying capacity (30/40kg).

We have made every effort to ensure that the information presented is accurate and complete. However, we are not responsible for the accuracy and completeness of the data and, in particular, we cannot guarantee that this specification does not contain errors or mistakes. The information contained in this specification may be changed at any time without notice.