



### EmiterNet 19" non-divided wall-mounted cabinet, unassembled, D 450mm

code: EM/AS6406X

- EM/AS6409X
- EM/AS6412X
- EM/AS6415X
- EM/AS6418X

## Description and Technical Characteristics of the Product:

The framework of the cabinet is made of steel sheet, designed for self-assembly - sold in boxes, in an unassembled form.

The enclosure has two cable exit holes (370x60mm 1x top section, 1x bottom section).

Front door with glued-in glass and 1-point lock, mounted on hinges that allow the door to open 180 degrees.

Removable side covers with lock.

Two 19" planes of vertical mounting profiles, mounted on horizontal beams with grille, every 15mm, minimum distance from the front door 60mm.

There are holes in the roof of the cabinet adapted for the installation of 2 ventilation modules (2 fans).

A 300mm long grounding cord.

Fixed shelf 250mm and 15 mounting screws included as standard.

The cabinets are designed for indoor use.

There are also longitudinal knockouts in the bottom and roof of the cabinets to allow the insertion of cables.

### **Technical parameters:**

Cabinet colour RAL 7035 (light grey - structure)

Two 19" mounting planes

Degree of protection against solids and dust and against water ingress: IP 20 (does not apply to cabinets with punched holes for cable entry).

Cabinet for self-assembly (unassembled). The cabinets are packed in cardboard boxes.





## Data Sheet



### **Compatible products (examples):**

19" fixed shelf, 1U, D 250mm, front-mounted RAL 7044 grey, code: EM/JE06-250 19" movable shelf, 1U, for keyboard, D 270/295 mm, RAL 7044 grey, code: EM/JE10 EmiterNet 19" 9-socket power strip, with earth pin, Uni-Schuko plug, 2m cable, LED indicator light, code: EM/LZ19.09F.2S.L EmiterNet 19" 9-socket power strip with earth pin, Uni-Schuko plug, 2m cable, On/off switch, code: EM/LZ19.09F.2S.W EmiterNet cabinet key lock for side doors with code no.: EM/JC-01

Note: shelves and grommets dedicated to EM/APxxxx cabinets, for example EM/SH-J018W-280, are not compatible.

# Related products: unassembled wall cabinets with a depth of 600mm - see the corresponding data sheets for these products (EM/AS66xx).

Cabinets:

code	carrying capacity	width	depth	height U	height	weight [kg]
EM/AS6406X	50kg	600	450	6U	370	18
EM/AS6409X	50kg	600	450	9U	500	23
EM/AS6412X	50kg	600	450	12U	635	24
EM/AS6415X	50kg	600	450	15U	770	27
EM/AS6418X	50kg	600	450	18U	910	30

Note: dimensions are given in millimetres!

We have made every effort to ensure that the information presented is accurate and complete. However, we are not responsible for the accuracy and completeness of the data and, in particular, we cannot guarantee that this specification does not contain errors or mistakes. The information contained in this specification may be changed at any time without notice.