

EmiterNet 19" non-divided wall-mounted cabinet, unassembled, D 600mm

code: EM/AS6606X

EM/AS6609X

EM/AS6612X

EM/AS6615X

Description and Technical Characteristics of the Product:

The framework of the cabinet is made of steel sheet, designed for self-assembly - sold in boxes, in an unassembled form.

The enclosure has two cable exit holes (370x60mm 1x top section, 1x bottom section).

Front door with glued-in glass and 1-point lock, mounted on hinges that allow the door to open 180 degrees.

Removable side covers with lock.

Two 19" planes of vertical mounting profiles, mounted on horizontal beams with grille, every 15mm, minimum distance from the front door 60mm.

There are holes in the roof of the cabinet adapted for the installation of 2 ventilation modules (2 fans).

A 300mm long grounding cord.

Fixed shelf 400mm and 15 mounting screws included as standard.

The cabinets are designed for indoor use.

There are also longitudinal knockouts in the bottom and roof of the cabinets to allow the insertion of cables.



Technical parameters:

Cabinet colour RAL 7035 (light grey - structure)

Two 19" mounting planes

Degree of protection against solids and dust and against water ingress: IP 20 (does not apply to cabinets with punched holes for cable entry).

Cabinet for self-assembly (unassembled). The cabinets are packed in cardboard boxes.

Data Sheet

Compatible products (examples):

19" fixed shelf, 1U, D 250mm, front-mounted RAL 7044 grey, code: EM/JE06-250

19" fixed shelf, 1U, D 350 mm, front-mounted RAL 7044 grey, code: EM/JE06-350

19" movable shelf, 1U, for keyboard, D 270/295 mm, RAL 7044 grey, code: EM/JE10

EmiterNet 19" 9-socket power strip, with earth pin, Uni-Schuko plug, 2m cable, LED indicator light, code: EM/LZ19.09F.2S.L

EmiterNet 19" 9-socket power strip with earth pin, Uni-Schuko plug, 2m cable, On/off switch, code: EM/LZ19.09F.2S.W

EmiterNet cabinet key lock for side doors with code no.: EM/JC-01

Note: shelves dedicated to EM/APxxxx cabinets, for example EM/SH-J018W-410, are not compatible.

Related products: unassembled wall cabinets with a depth of 450mm - see the corresponding data sheets for these products (EM/AS64xx).

Cabinets:

| code | carrying capacity | width | depth | height U | height | weight [kg] |
|------------|-------------------|-------|-------|----------|--------|-------------|
| EM/AS6606X | 50kg | 600 | 600 | 6U | 370 | 22 |
| EM/AS6609X | 50kg | 600 | 600 | 9U | 500 | 25 |
| EM/AS6612X | 50kg | 600 | 600 | 12U | 635 | 28 |
| EM/AS6615X | 50kg | 600 | 600 | 15U | 770 | 31 |

Note: dimensions are given in millimetres!

We have made every effort to ensure that the information presented is accurate and complete. However, we are not responsible for the accuracy and completeness of the data and, in particular, we cannot guarantee that this specification does not contain errors or mistakes. The information contained in this specification may be changed at any time without notice.