

Data Sheet

Single-module straight adapter 22.5x45mm, white; code: DC/FA-644-1SP

Description and Technical Characteristics of the Product:

Adapter in 45x45 standard, size 45x45 (one module) for telephone and ICT keystone sockets, such as RJ45 or RJ12. Designed for the installation of one socket.

Installation of the adapter by snapping into UCHKP quick-mount bracket, OBUK surface-mount enclosure, RAMK masking frame.



Markings:

Single-module straight adapter 22.5x45mm, white; code: DC/FA-644-1SP

Products compatible with the adapter:

UTP RJ45 Cat.5e keystone blue, code: DCN/FA-682MK-8-C5E

UTP RJ45 Cat.5e keystone blue, tool-free, code: DCN/FA-S682MK-8-C5E

UTP RJ45 Cat.5e keystone white, code: DC/FA-682MK-8-C5E

STP RJ45 Cat.5a keystone blue, code: DCN/FA-682MKSF-8-C5e

STP RJ45 Cat.5e keystone white, code: DC/FA-682MKSF-8-C5E

UTP RJ45 Cat.6 keystone blue, code: DCN/FA-1090-8-C6

UTP RJ45 Cat.6 keystone blue, tool-free, slim code: EM/UQK-C6

STP RJ45 Cat.6 keystone blue, code: DCN/FA-1090SF-8-C6

STP RJ45 Cat.6 keystone blue, tool-free, slim code: EM/SQKSS-C6

STP RJ45 Cat. 6A keystone blue, tool-free, slim, code: EM/SQKSS-C6A

Technical parameters:

Mechanical:

colours: white

dimensions (W x H): 22.5x45mm

material: ABS

Note: The adapters are not suitable for sockets other than RJ45/R12, such as HDMI, BNC- type, F-type etc. In these cases, use our other adapters without the dust cap.

We have made every effort to ensure that the information presented is accurate and complete. However, we are not responsible for the accuracy and completeness of the data and, in particular, we cannot guarantee that this specification does not contain errors or mistakes. The information contained in this specification may be changed at any time without notice.