

19" 1U 24xSC duplex sliding optical distribution box, grey; Code: EM/PS-1924SCD0-S

Description and Technical Characteristics of the Product:

The optical distribution box is designed for installation in 19-inch standing and wall ICT cabinets. It has 24 holes, made for mounting SC Duplex adapters, and it is equipped with a pull-out drawer. The optical distribution box comes with one double fibre cassette, designed to accommodate up to 24 splices (2 x 2 x 6) and two PG 13.5 glands.



Markings:

19" 1U 24xSC duplex sliding optical distribution box, grey; code: **EM/PS-1924SCD0-S**

Products compatible with the optical distribution box:

EM/ADSCUPCSMDX	SC duplex mono-mode adapter, blue
EM/ADSCAPCSMDX	SC APC duplex mono-mode adapter, green
EM/ADLCPCSMQD	LC quad (2 x duplex) adapter mono-mode, blue
BK/104ADS30	SC/SC APC duplex mono-mode adapter in metal enclosure
BK/104ADM20.C	SC/SC PC duplex multi-mode adapter in plastic enclosure
BK/104AQM60	LC/LC PC 2xduplex multi-mode adapter

Technical parameters:

Mechanical:

colour - grey

dimensions (WxDxH) 478x242x44 mm

material: powder-coated steel

Notes:

It is possible to secure up to 48 splices after exchanging the optical distribution box cassette with EM/KAS-SW0 fiber optic cassettes (up to four cassettes securing 12 splices each), thus using the full potential of the optical distribution box (it is necessary to remove the covers between the cassettes, cassette fastening screw not included).

Data Sheet

We have made every effort to ensure that the information presented is accurate and complete. However, we are not responsible for the accuracy and completeness of the data and, in particular, we cannot guarantee that this specification does not contain errors or mistakes. The information contained in this specification may be changed at any time without notice.