
19" 1U 24xSC simplex (24xLC Duplex) sliding optical distribution box, grey, code: EM/PS-1924SCS0-S

Description and Technical Characteristics of the Product:

The optical distribution box is designed to be mounted in 19-inch standing and wall-mounted ITC cabinets. It has 24 holes, made for mounting SC Simplex (or LC duplex) adapters and it is equipped with a pull-out drawer. The optical distribution box comes with one double fibre cassette, designed to easily accommodate 48* splices (each cassette has two guides with six grooves for splice covers, two splice covers can be easily secured in each groove), two PG 13.5 glands are also provided. The optical distribution box has a number of convenient features, such as guides for arranging excess pigtail and holes for zip ties in order to secure the cable in place.



*a skilled fitter is able to secure up to 72 splices in the box, if three splice covers are snapped-in in each groove; this is not recommended, due to the difficult management of 72 splices in a 1U high optical distribution box

Markings:

19" 1U 24xSC simplex sliding optical distribution box, grey; code: **EM/PS-1924SCS0-S**

Products compatible with the optical distribution box:

EM/ADSCUPCSMSX	SC simplex mono-mode adapter blue
EM/ADSCAPCSMSX	SC APC simplex mono-mode adapter green
EM/ADLCPCSM DX	LC duplex mono-mode adapter blue
BK/104ASM20.C	SC/SC PC simplex multi-mode adapter in plastic enclosure
BK/104ASS30	SC/SC APC simplex mono-mode adapter in metal enclosure
BK/104ADM60	LC/LC PC duplex multi-mode adapter

Technical parameters:

Colour: grey

Dimensions (WxDxH): 478x242x44mm

Finish material: powder-coated steel

We have made every effort to ensure that the information presented is accurate and complete. However, we are not responsible for the accuracy and completeness of the data and, in particular, we cannot guarantee that this specification does not contain errors or mistakes. The information contained in this specification may be changed at any time without notice.