

Plugs: RJ9, RJ11, RJ12, RJ45

Markings:

RJ9 (4P4C) plug, Code: EM/X-ML-4P4C

RJ11 (6P4C) plug, Code: EM/X-ML-6P4C

RJ12 (6P6C) plug, Code: EM/X-ML-6P6C

RJ45 UTP plug Cat. 5e universal (8P8C), Code: EM/X-ML-5U-8P8C

Wtyk RJ45 STP kat. 5e shielded (8P8C), Code: EM/X-ML-5F-8P8C



Description and Technical Characteristics of the Product:

The plugs are used to terminate both unshielded and shielded ICT ca
Their dimensions are in accordance with
PN/EN 50173 and, depending on the type, they have 4, 6 or 8 contac
Used in various types of ICT and
computer equipment.



Technical parameters:

Colour: transparent

Finish material: plastic

Weight: 1.4g

Mechanical parameters:

RJ Plug: 500 plug-in cycles

Cable size: 24 to 26 AWG

Operating temperature: -10°C to +68°C,

Humidity: 10% to 90%

We have made every effort to ensure that the information presented is accurate and complete. However, we are not responsible for the accuracy and completeness of the data and, in particular, we cannot guarantee that this specification does not contain errors or mistakes. The information contained in this specification may be changed at any time without notice.