

Data Sheet

F-type female socket in 22.5x45 adapter, white; code: FU/FA-2420-RF

Description and Technical Characteristics of the Product:

F-type female socket in adapter 22.5x45 (1 module), 45x45 mounting standard, connection of cables to the F-type female connector. It is characterised by a compact design so that it can be used in cable ducts as deep as 40mm. Designed for use in ICT systems, audio/video systems, TV and CCTV.

Mounting by snapping into UCHKP quick-mount bracket, OBUK surface-mount enclosure, RAMK masking frame.



Markings:

F-type female socket in 22.5x45 adapter, white; code: FU/FA-2420-RF

Products compatible with the socket:

mounting frames:

2-module masking frame with metal bracket, for ducts: KP90x60, 110x60, 130x60, 150x60 and PU-2 boxes code: RAMK-2/M

4-module masking frame with metal bracket, for ducts: KP90x60, 110x60, 130x60, 150x60 and PU-4 boxes, code: RAMK-4/M

6-module masking frame with metal bracket, for ducts: KP90x60, 110x60, 130x60, 150x60 and PU-6 boxes, code: RAMK-6/M

complete surface-mount enclosures:

2-module surface-mount enclosure for 45x45mm standard fixtures (includes metal SUP bracket and RAM frame) code: OBUK-2/M

4-module surface-mount enclosure for 45x45mm standard fixtures (includes metal SUP bracket and RAM frame) code: OBUK-4/M

6-module surface-mount enclosure for 45x45mm standard fixtures (includes metal SUP bracket and RAM frame) code: OBUK-6/M

quick-mount brackets in the ducts

2-module holder-frame for KP 90x40, 90x60, 110x60, 150x60, code: UCHKP-2

4-module holder-frame for KP 90x40, 90x60, 110x60, 150x60, code: UCHKP-4

6-module holder-frame for KP 90x40, 90x60, 110x60, 150x60, code: UCHKP-6



Data Sheet

Technical parameters:

Mechanical:

colour: white

dimensions (W x H x D): 22.5x45x33mm

weight: 18g

Socket:

Connector type: F female/F female

Operating temperature: -10°C to +68°C,

Humidity: 10 to 90%