

## Data Sheet


---

### Speaker socket in 22.5x45 adapter, white; code: FU/FA-2420-SP

#### Description and Technical Characteristics of the Product:

Speaker (screw) socket in adapter 22.5x45 (1 module), 45x45 mounting standard, connection of cables to double screw connector. It is characterised by a compact design so that it can be used in cable ducts as deep as 40mm. Designed for use in ICT and audio/video systems.

Mounting by snapping into UCHKP quick-mount bracket, OBUK surface-mount enclosure, RAMK masking frame.



#### Markings:

Speaker socket in 22.5x45 adapter, white; code: FU/FA-2420-SP

#### Products compatible with the socket:

mounting frames:

2-module masking frame with metal bracket, for ducts: KP90x60, 110x60, 130x60, 150x60 and PU-2 boxes code:

RAMK-2/M

4-module masking frame with metal bracket, for ducts: KP90x60, 110x60, 130x60, 150x60 and PU-4 boxes, code:

RAMK-4/M

6-module masking frame with metal bracket, for ducts: KP90x60, 110x60, 130x60, 150x60 and PU-6 boxes, code:

RAMK-6/M

complete surface-mount enclosures:

2-module surface-mount enclosure for 45x45mm standard fixtures (includes metal SUP bracket and RAM frame) code:

OBUK-2/M

4-module surface-mount enclosure for 45x45mm standard fixtures (includes metal SUP bracket and RAM frame) code:

OBUK-4/M

6-module surface-mount enclosure for 45x45mm standard fixtures (includes metal SUP bracket and RAM frame) code:

OBUK-6/M

quick-mount brackets in the ducts

2-module holder-frame for KP 90x40, 90x60, 110x60, 150x60, code: UCHKP-2

4-module holder-frame for KP 90x40, 90x60, 110x60, 150x60, code: UCHKP-4

6-module holder-frame for KP 90x40, 90x60, 110x60, 150x60, code: UCHKP-6



## **Data Sheet**

---

### **Technical parameters:**

Mechanical:

colour: white

dimensions (W x H x D): 22.5x45x33mm

weight: 18g

Socket:

Connector type: 2x screw terminal/2x screw terminal

Operating temperature: -10°C to +68°C,

Humidity: 10 to 90%