

Data Sheet

USB 3.0 A female keystone socket, white; code: EM/KEY-USB3.0-A/A-DC

Description and Technical Characteristics of the Product:

USB 3.0 A female keystone socket (on both sides) can be mounted in keystone adapters with dimensions (H x W) of 16.10x14.50mm, such as 45x45 socket adapters, electrical equipment frames, modular panels, etc. Designed for use in ICT systems, audio/video systems, etc.



Markings:

USB 3.0 A female keystone socket, white; code: EM/KEY-USB3.0-A/A-DC

Products compatible with the socket:

FU/FA-644-8MP 45x45 1xRJ45,12 adapter

FU/FA-644-9MP 45x45 2xRJ45,12 adapter

DCN/3012KX-24 19" 24 x RJ45 UTP (1U) panel for tool-free sockets, unshielded, unarmoured, blue, with colour-coded markers

DCN/3012KX12BL 10" 12-port panel, blank, for RJ45 and RJ12 for tool-free sockets

Note:

1. The special keystone sockets are not compatible with adapters equipped with a dust cap.
2. Due to the different depth of the sockets and the different ways of routing and connecting the cables, the socket may not be compatible with some products (boxes, ducts, etc.).
3. If the sockets extend beyond the face of the adapter, they may not be compatible with some products.
4. The correct operation of the socket is dependent on all the elements present in the signal path.

Due to the possibility of different combinations of products, it is recommended to check this or contact the technical department before installation.

Data Sheet

Technical parameters:

Mechanical:

colour: white

dimensions (W x H x D): 16.70x21.70x40.70mm

Connector type: USB 3.0 A female/USB 3.0 A female

Operating temperature: 0°C to +40°C

Humidity: 10 to 80%

We have made every effort to ensure that the information presented is accurate and complete. However, we are not responsible for the accuracy and completeness of the data and, in particular, we cannot guarantee that this specification does not contain errors or mistakes. The information contained in this specification may be changed at any time without notice.