

Data Sheet

RJ45 UTP Cat.5e ICT socket, with adapter 1-module white, low, code: DCN/TS-868K-8-C5E

Description and Technical Characteristics of the Product:

UTP RJ45 socket Cat.5e with adapter 1-module white, It is characterised by a compact design so that it can be used in cable ducts as deep as 40mm, it has a dust shutter, IDC connector cover. The socket has a 568B-type colour-coded connection sequence marking.



Products compatible with the socket:

panels:

19" panel, 24xRJ45 UTP Cat.5e (1U) blue, code: DCN/PPFA652K248C5E

19" panel, 48xRJ45 UTP Cat.5e (2U) blue, code: DCN/PPFA652K488C5E

Cables:

Emiter Net UTP Cat.5e, wire 4x2x23AWG code: K/EMITERNET-UTP5EPVC.

Technical parameters:

Mechanical:

colour - white

dimensions (W x H x D) – 22.5x45x23

weight - 14g

Socket:

IDC-LSA type connector

material: PC enclosure, UL 94V-0

IDC contact: phosphor bronze, coated with 100-micron nickel layer, outer layer: 200-micron tin

Contacts in RJ45 socket - phosphor bronze pins coated with 100-micron nickel layer, outer layer: 50-micron gold

Mechanical parameters:

RJ45 socket - 750 plug-in cycles

IDC connector - 200 connection cycles

Cable size 24 to 26 AWG

Operating temperature: -10°C to +68°C,

Humidity - 10% to 90%

Data Sheet

Electrical parameters:

Maximum current value 1.5A

Maximum voltage 150V

Maximum contact resistance 20mΩ

Minimum insulation resistance 500MΩ

Transmission parameters:

Transmission parameters in accordance with PN - EN 50173 EIA/TIA 568B ISO/IEC 11801 2nd ed.; IEC 61156-6; EN 50288-4-2

Certificates:

[The National Institute of Telecommunications Confirmation of Conformity with the following standards: PN/EN 50173; ISO/IEC 11801](#)