

Fox SMART LAN SMART L 3.0



Easy Installation

Plug and play installation.



Strong Signal

Strong LAN signal for maximum range



IP65 Rated

Suitable for outdoor installation.



Remote Monitoring

Connect to the FoxCloud.

The Smart L3.0 is an intelligent LAN enabled device allowing you to monitor the status and performance of your Fox PV system via the FoxCloud remote monitoring platform. The Smart L 3.0 is ideal in situations where there is no reliable WiFi or GPRS connection available.

System owners and installers can easily keep up-to-date with performance data in real-time, view historic records and monitor system alerts.

- Stable lan communication
- IP65 protection class
- Vodafone, Tata, Aircel and Airtel compatible
- Clean and compact design
- User-friendly monitoring app
- Plug and play installation
- Monitor your system from anywhere
- 24/7 monitoring



Fox SMART LAN

SMART L 3.0

SPECIFICATIONS

Product Name	Smart L 3.0
Dimensions [mm]	100.0 x 49.0 x 28.0
Weight [g]	55
Input Voltage	DC7-12V
Power	1W(MAX)
Ethernet Speed	10M/100M
Interface	RS485
Parameter	9600/8/n/1(default)
Green LED	Receive Data from Inverter
Red LED	Work status
connector	USB
Temperature	-20°C-+60°C
Humidity	≤95%, NO
Altitude	≤4000M
IP Grade [°C]	IP65
Fire rating [%]	UL94V-0
UV immunity	F1

