

Low Voltage Battery 5 to 10 kWh

# Low voltage Battery



Models:  
Ai-LB 5K  
Ai-LB 10K



## Safety

- LFP safe technology
- All-round BMS protection



## Reliable

- IP65 rated design for outdoor use
- High quality cell inside



## User-friendly

- Remote upgrade
- Online monitoring via Solplanet apps



AUTHORIZED DISTRIBUTOR:



PORCELANOWA 27  
40-241 KATOWICE

emiter@emiter.net.pl  
+48 32 730 34 00

[www.emiter.net.pl](http://www.emiter.net.pl)

# Technical Datasheet

Ai-LB 5K

Ai-LB 10K

	Ai-LB 5K	Ai-LB 10K	
System Data	Cell type	LiFePO4	
	Battery module	LB51100A	
	Module number	1	2
	Nominal capacity	5.12 kWh	10.24 kWh
	Nominal battery voltage	51.2 V	
	Battery voltage range	44.8 V - 57.6 V	
	Max. charging / discharging current	50 A	100 A
	Max. charging / discharging power	2.56 kW	5.12 kW
General Data	Dimensions(W/D/H)	490 / 150 / 680 mm	640 / 181 / 1017 mm
	Module weight	44.5 kg	
	Weight	57 kg	116 kg
	Installation location	indoor / outdoor	
	Mounting method	Floor stand	Floor stand / Wall Mount
	Operating temperature range	Charge: 0°C ~ 55°C Discharge: -20°C ~ 55°C	
	Storage temperature range	-20°C ~ 55°C	
	Cooling concept	Natural convection	
	Degree of protection	IP65	
	Relative humidity	5~95%, non-condensing	
	Max. operating altitude	3000m	
	Scalability	Max.8 sets in parallel	Max.4 sets in parallel
	Communication	CAN	
	Certification	TUV/IEC 62619/IEC 62040/IEC 61000/UN38.3	
Warranty	10 Years		

Version: Nov 2022