



- DESIGN: MODULAR
- DEGREE OF PROTECTION: IP65
- YEARS OF WARRANTY: 5
- UV RESISTANCE: YES
- READY TO CONNECT: YES
- WEIGHT: 1.01 KG



The connection panel from the Polish manufacturer EMITER provides protection against the effects of both indirect and direct discharges on the direct current side. It is designed for use in grounded and isolated photovoltaic installations. Due to the high degree of IP protection, outdoor installation is possible. The design of the switchgear is intended for surface mounting. Depending on the equipment, switchboards can perform various functions.

### BASIC PARAMETERS DC SIDE

Number of inputs   PV string outputs	1   1
Quantity   Type of DC surge arrester   Type	1   Noark   T1/T2
Connection type	Array MC4 Stäubli

### ELECTRICAL AND MECHANICAL PARAMETERS OF THE HOUSING

Model	PHS 4 T
Number of fields	4
Dimensions of housing without chokes and MC4 (Length Width Height)	120.00   135.00   201.00
Design in accordance with	EN 60670-1, EN 62208
Level of security	IP65
Protection class	II
Rated insulation voltage $U_i$	400 V AC, 1500 V DC
The incandescent rod test	650°C
Impact resistance	IK08
UV resistance	YES
Recyclable plastic	bezhalogenowy
Working temperature	-25°C - +60°C

### DC surge arrester used (SPD)

Manufacturer / Model	Noark Ex9UEP1+2 6.25(R) 3P 1000
Made in accordance with	EN 61643-31
Surge protection	PV T1+T2 (Klasa I+II, B+C, Typ 1+2)
Making the insert	MOV (Warystor)
Protection function	thermal
Protection mode	+ → PE
-	- → PE
-	+ ↔ -
Maximum continuous operating voltage $U_{CPV}$	
+ → PE, - → PE	1000 V
+ ↔ -	1000 V
Frequency	DC
Nominal discharge current $I_n$ (8/20 $\mu$ s)	20 kA
Maximum discharge current $I_{max}$ (8/20 $\mu$ s)	40 kA
Surge current $I_{imp}$ (10/350 $\mu$ s)	
+ → PE, - → PE	6.25 kA
+ ↔ -	6.25 kA
Voltage protection level $U_p$ by $I_n$	
+ → PE, - → PE	3.8 kV
+ ↔ -	3.8 kV
Leakage current $I_{PE}$ by $U_{REF}$ DC	< 50 $\mu$ A
Leakage current $I_{PE}$ by $U_{REF}$ AC	< 1 mA
Maximum short-circuit current $I_{SCPV}$	1000 As
Number of ports	1
LV system type	DC, niezziemiony system PV
Auxiliary contact (optional)	1 przemienny (CO)
Auxiliary contact, voltage / current	
AC $U_{max}$ / $I_{max}$	250 V AC / 1 A
DC $U_{max}$ / $I_{max}$	250 V DC / 0.1 A; 75 V DC / 0.5 A
Connection configuration	Y



